

Idemitsu CVTF

Description

Idemitsu CVTF is the latest technologically advanced continuous variable transmission fluid suitable for use in all modern CVT units. This special formulation consists of high quality hydro cracked base stock and various additives to enhance smooth & positive shifting under severe working conditions.

Application

Recommended for all modern continuous variable transmission gearbox, especially Japanese cars.

Compatible with:

Amix CVT Fluid-DC, CVT Fluid TC, CVT Fluid NS-1 / NS-2, CVTF 3320, Dia-Queen CVT Fluid-J1, ECVT Fluid / i-CVT Fluid, SCVT Fluid, CVT Oil, CVT Fluid Green-1 / Green IV, CVT Fluid 3320, Matic Fluid D, i-CVT/FG.

For more details please refer to the Idemitsu ATF / CVTF comparable table Chart.

Characteristics

1. Super long-life continuously variable transmission fluid.
2. Superior protection against premature wear & tear of moving parts.
3. Excellent protection and performance at high temperatures and high loads.

Packaging

6 x 4 Litres Carton, 20 Litres Pail

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.

Lubricant Product Information

Typical Specifications

Idemitsu CVTF

	ASTM METHOD	
Color (Appearance)		Green
Density 15 °C g/cm ³	D-4052	0.8525
Flash Point (COC) °C	D-92	206
Viscosity, cSt @ 40 °C	D-445	30.93
@ 100 °C	D-445	7.006
Viscosity, mPa-s @ -40 °C	D-2983	8550
Viscosity Index	D-2270	199
Pour Point °C	D-6749	-45.0
TAN,(mgKOH/g)	D-664	0.84
Foaming @ 93.5 °C	D-892	0-0

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.